



EU-Declaration of Performance

In accordance with Annex III of Regulation (EU) No.305/2011
(Construction Product Regulation)

For the product "**SUPERTECTUM**"
No: CPR 18/0188

1. Unique identification code of the product-type:
ETAG 005, Part 1 & Part 6
2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):
Batch number: See product label under "LOT"
3. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:
ETAG 005, Part 1 & Part 6
Liquid Applied Roof Waterproofing Kit, based on Polyurethane
4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):
ETS EUROPE BVBA
HERENTALSEBAAN 406 D1
B-2160 WOMMELGEM BELGIUM
5. Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2):
Not Relevant
6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:
System 3
7. In case of the declaration of performance concerning a construction product covered by a harmonized standard:
Not relevant
8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:
The notified body (0761):

Instituto De Ciencias De la Construccion Eduardo Torroja
C/Serrano Galvache n4
28033 Madrid

Issued **ETA-18/0188**

on the basis of **ETAG 005 part 6**

has carried out determination of the product-type on the basis of type testing (based on sampling carried out by the manufacturer), type calculation, tabulated values or descriptive documentation of the product.

9. Declared performance

ETAG 005 – part 1 & part 6

The product is used for the waterproofing of roof against the water, as in liquid or in vapor form, and it is consisting of components:

SUPERTECTUM UV
GEOTEXTEIL (optional)
SUPERTECTUM TOPCOAT 440 (optional)

Performance determined

Essential characteristics	Performance	Harmonized technical specification
Minimum thickness	1.2 mm	ETAG 005 Part 6
Water vapour diffusion resistant factor		ETAG 005 Part 6
Resistance to wind loads		ETAG 005 Part 6
Resistance to plant roots		ETAG 005 Part 6
Statement on dangerous substances		ETAG 005 Part 6
Resistance to slipperiness		ETAG 005 Part 6

	Supertectum UV	Supertectum UV + Supertectum TOP COAT 440
External fire performance	Broof (t1)	
Fire reaction	Class F	
Expected working life	W3 (25 years)	W2 (10 years)
Climatic zone of use	S (Severe)	
User loads	P1	P3
Roof slopes	S1 to S4	
Minimum surface temperatures	TL3 (-20°C)	
Maximum surface temperatures	TH4 (90°C)	TH3 (80°C)

NPD: No Performance Determined

ETS EUROPE BVBA
Herentalsebaan 406 D1.
B-2160 Wommelgem

Belgium
Tel: +32 3 227 28 58
Fax: +32 3 475 16 66



www.ETS-EUROPE.BE

Where pursuant to Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies: Not applicable

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:
de Potter Jean-Luc

CEO