

Wommelgem, 07/12/2018



EU-Declaration of Performance

In accordance with Annex III of Regulation (EU) No.305/2011 (Construction Product Regulation)

For the product "SUPERTECTUM TX"

No: 2085-CPR-061/07.12.2018

1. Unique identification code of the product-type:

EN 1504-2

Principles: Ingress Protection (1.3); Moisture Control (2.2); Increasing Resistivity (8.2)

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

Batch number: See product label under "LOT"

3. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:

Surface Protection of concrete: coating.

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

ETS EUROPE BVBA

Herentalsebaan 406 D1

B-2160 Wommelgem, Belgium

5. Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2):

Not Relevant

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 2+

7. In case of the declaration of performance concerning a construction product covered by a harmonized standard:

EN 1504-2

The notified laboratory:

Eurotest-Control EAD (2085)

108 Besarabia St. 1517 Sofia, Bulgaria

has carried out determination of the product-type on the basis of type testing (based on sampling carried out by the manufacturer), and issued the following certificate of conformity of the factory production control: **No: 2085-CPR-061/07.12.2018**

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

Not relevant

9. Declared performance

Performance determined of **SUPERTECTUM TX**

Essential characteristics	Performance	Harmonized technical specification
Permeability to CO ₂	S _D >50 m	EN 1504-2
Permeability to water vapor	S _D <5 m Class I (permeable)	
Capillary absorption & permeability to water	W<0.1 kg/m ² ·h ^{0.5}	
Adhesion strength by pull-off test	≥1.5 (1.0) N/mm ²	
Adhesion strength after thermal compatibility	≥1.5 (1.0) N/mm ²	
Reaction to fire	Euroclass F	
Dangerous substances	In accordance with 5.3	
Artificial weathering according to EN 106211, for outside application -blistering -cracking -flaking -colour change	No change	

Where pursuant to Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies:

Not applicable

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

de Potter Jean-Luc

CEO